SPRAY / SPRAY BAR HYDRAULIC LIFT KO 600IH 16X14

Technical Specifications

MODEL	600IH 14 X 12	800IX 14 X 12	600IH 16 X 14	800IH 16 X 14
TANK CAPACITY	600	800	600	800
MATERIAL	POLYETHYLENE			
PUMP MODEL	3PH			
FLOW L / Min	80/100			
WORKING PRESSURE LB / POL ²	250PSI			
MAXIMUM ROTATION PUMP (RPM)	540			
SUPPLY	Anti-pollutant FAST FOR ALL MODELS			
SUPPLY FLOW L / Min	150/192			
SHAKER	HYDRAULIC FOR ALL MODELS			
COMMAND	MASTER OF TRACT 2 - (4-WAY OPTION)			
DISPLAY LEVEL	WITH GRADUATED SCALE FOR ALL MODELS			
CLEAN WATER TANK (L)	15	15	15	15
REQUIRED POWER (HP)	8/10	8/10	8/10	8/10
RAISE THE COURT AND BARS	PLUMBING FOR ALL MODELS			
OPENING BARS	PLUMBING FOR ALL MODELS			
BARS LENGTH (m)	12	12	14	14
BAR HEIGHT OF WORK (m)	0.40 A 1.50			
DOOR TIPS INSTALLED	DUPLEX-2 11002 CONE POTTERY polyacetal			
NUMBER OF DOOR TIPS	26	26	30	30
SPACING TIPS (m)	0.50 FOR ALL MODELS			
TIME MACHINE (m)	2.80	2.80	3.30	3.30
MACHINE WIDTH (m)	2.55	2.55	2.55	2.55
MACHINE LENGTH (m)	1.86	1.83	1.86	1.83
BACK MACHINE WEIGHT (Kg)	440	540	480	580