SPRAY / SPRAY BAR HYDRAULIC LIFT KO 1600 IH 16X14 HERBICANA

Technical Specifications

MODEL	KO-1400 HERBICANA IH16x14		KO-1600 HERBICANA IH16x14		KO-1400 HERBICANA IH14x12		KO-1600 HERBICANA IH14x12	
CAPACITY OF TANKS	FRONT	REAR	FRONT	REAR	FRONT	REAR	FRONT	REAR
	800	600	800	800	800	600	800	600
MATERIAL	POLYETHYLENE							
SHAKER	BOTH HYDRAULIC TANKS FOR ALL MODELS							
DISPLAY LEVEL	WITH GRADUATED SCALE FOR ALL MODELS							
PUMP MODEL	3PH 100							
FLOW L / Min	100							
COMMAND	MASTER OF 4VIAS							
Incorporator DEFENSIVE	MIX OF 15 LITERS WITH GUN IN TWO TANKS (OPTIONAL)							
BAD PRESSURE? MAXIMUM WORKING LB / POL ²	250PSI							
ABASTECIMANTO	HITCH RA? FAST							
MAXIMA ROTATING PUMP (RPM)	540							
RECOMMENDED TRACTOR (HP)	100							
SPEED BAD? X. WORK	12km / h							
RAISE THE COURT AND BARS	HYDRAULIC FOR ALL MODELS							
OPENING OF THE BAR	HYDRAULIC FOR ALL MODELS							
BAR LENGTH (m)	14		14		12		12	
BAR HEIGHT OF WORK (m)	0.40 to 1.50							
DOOR TIPS INSTALLED	DUPLEX KO							
TIPS INSTALLED	CONE EMPTY		FAN		CONE EMPTY		FAN	
NUMBER OF DOOR TIPS	30		30		26		26	
SPACING TIPS (m)	0.50 FOR ALL MODELS							
TIME MACHINE (m)	3.3		3.30		2.60		2.80	
Machine Width (m)	2.35		2.35		2.35		2.00	
MACHINE LENGTH (m)	1.95		1.90		1.95		1.90	
BACK MACHINE WEIGHT (Kg)	490		580		440		540	