SPRAY / SPRAY BAR HYDRAULIC LIFT KO 800 IH16

Technical Specifications

MODEL	KO-600 IH16	KO-800 IH16	KO-800 IH18
TANK CAPACITY	600	800	800
MATERIAL	POLYETHYLENE		
PUMP MODEL	3PH		
FLOW L / Min	100		
WORKING PRESSURE LB / POL ²	250PSI		
SPIN BAD? MAXIMUM PUMP (RPM)	540		
SUPPLY	FAST ANTI POLLUTANT FOR ALL MODELS		
SUPPLY FLOW L / I	192		
SHAKER	HYDRAULIC FOR ALL MODELS		
COMMAND	MASTER OF 4VIAS		MASTER OF CABLE 4VIAS
DISPLAY Ni? SPEED	WITH GRADUATED SCALE FOR ALL MODELS		
Incorporator DEFENSIVE	15 LITER (OPTIONAL)	MIX 15 LITRE	MIX 25 LITRE
Á RESERVOIR? WATER CLEAN (Litres)	15	15	15
REQUIRED POWER (HP)	10	10	10
RAISE THE COURT AND BARS	Hydra? ULICO FOR ALL MODELS		
OPENING OF THE BAR	Hydra? ULICO FOR ALL MODELS		
BAR LENGTH (m)	16	16	18
BAR HEIGHT OF WORK (m)	0.50 to 1.40		
DOOR TIPS INSTALLED	DUPLEX KO		
NUMBER OF DOOR TIPS	32	32	36
TIPS	FAN / CONE EMPTY	FAN / CONE EMPTY	FAN / CONE EMPTY
SPACING TIPS (m)	0.50 FOR ALL MODELS		
TIME MACHINE (m)	3.37	3.37	3.37
Machine Width (m)	2.55	2.55	3.20
MACHINE LENGTH (m)	1.86	1.86	2.00
WEIGHT OF EVIL? BACK MACHINE (Kg)	460	560	800